

M12 to RJ45 ETHERNET ADAPTER 90°

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Image:

Part No.: MC04P2RSDSB-RJ5E

Contacts Poles: 04 Pin

Connector Gender: Female connector

Current Rating: 4 A

Keyway Coding: D-Coding

EMC Shielding: Un-shielded

Product data

04 Pin	Connector Gender:	Female connector
4 A	Voltage Rating:	250V
D-Coding	EMC Shielding:	Un-shielded
180° Straight	Contacts Termination:	PCB dip soldering
-40°C ~ + 105°C	Contacts Material:	Phosphor bronze, machined solid pin
3μ" Gold plating thickness	Inserts:	PA66 + GF
Epoxy resin, O-Ring	Housing/ Outer Shell:	Brass with nickel plasting
Brass with nickel plated	Contact Resistance:	≤5mΩ
PG9, M16x1.5	Insulation Resistance:	≥ 100 MΩ
IP 67	Pollution Degree:	III
UL94 V0	Waterproof Depth:	IP67 1m depth 30 minutes, IP69K against high pressure/ steam jet
500 times	Warranty:	2-years quality guarantee period
RoHS compliant, REACH compliant	Reference Standard:	IEC 61076-2-101
III Cartified CE/EMC ID67 ID60K	Connector Type:	Panel mount receptacle
of Certified, OL/ LIVIO, IF 07, IF 09K	Connector Type.	i dilci illoditi reocptacie
	A A D-Coding 180° Straight 40°C ~ + 105°C Bµ" Gold plating thickness Epoxy resin, O-Ring Brass with nickel plated PG9, M16x1.5 P 67 UL94 V0 500 times	Voltage Rating: D-Coding EMC Shielding: Contacts Termination: Contacts Material: Su" Gold plating thickness Epoxy resin, O-Ring Housing/ Outer Shell: Contact Resistance: PG9, M16x1.5 Insulation Resistance: P67 Pollution Degree: UL94 V0 Waterproof Depth: COMBAN Warranty: Warranty: RoHS compliant, REACH compliant Reference Standard:

Description