

M12 D-Code 4Pin female field wireable (assembly type) connector, screw connection, 4.0-7.0 mm cable outlet, 360° shielded

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Image:

Part No.: MC04A2LWDSB

Contacts Poles: 04 Pin

Connector Gender: Female connector

Current Rating: 4 A

Wire Gauge (size): 22AWG/ 0.34mm², 20AWG/

Keyway Coding: D-Coding

EMC Shielding: 360° fully shielded

Product data

Contacts Poles:	04 Pin	Connector Gender:	Female connector
Current Rating:	4 A	Wire Gauge (size):	22AWG/ 0.34mm ² , 20AWG/ 0.5mm ² , 18AWG/ 0.75mm ²
Voltage Rating:	250V	Keyway Coding:	D-Coding
EMC Shielding:	360° fully shielded	Straight/ 90° Angled:	180° Straight
Contacts Termination:	Screwing	Temperature Rating:	-40°C ~ + 105°C
Contacts Material:	Phosphor bronze, machined solid pin	Contacts Plating:	3μ" Gold plating thickness
Inserts:	PA66 + GF	Sealing:	O-Ring
Housing/ Outer Shell:	Brass with nickel plating	Locking Screws:	Brass with nickel plated
Contact Resistance:	≤5mΩ	Insulation Resistance:	≥ 100 MΩ
Protection Degree:	IP 67	Pollution Degree:	III
Connector Flamability:	UL94 V0	Waterproof Depth:	IP67 1m depth 30 minutes
Plug Mating Life:	500 times	Suitable Cable Diameter:	PG9 (4.5 ~ 7mm)
Warranty:	2-years quality guarantee period	Compliance:	RoHS compliant
Reference Standard:	IEC 61076-2-101	Connector Type:	Field assembly type

Description

The M12 metric size D-Coding connectors, based on IEC 61076-2-101 standard, it is the most commonly used connector in the industrial ethernet cabling. CABLEFORCE M12 D-Coding connectors are developed and designed for harsh industrial and climatic environments, e.g. High temperature range endurance, Hydrolysis resistant, Oil resistant, Corrosion resistant, UV-Resistant, Abrasion resistant.

- Cableforce field wireable connector is available with contacts: 3pin, 4pin, 5pin, 8pin, 12pin
- We also sell the related bulk cables with unshielded, shielded, oil resistant, hydrolysis resistant, UV-resistant options
- The receptacle counter part with PCB contacts or Solder type panel mount connectors with wires
- Operating voltage 250V/ 60V/ 30V;
- Current range: 4A, 2A, 1.5A
- Degree of protection IP67