


## M12 X-Code 8Pin male to RJ45 male, molded 10Gbps Cat 6A 4x2x26AWG PUR halogen free cable

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!





Part No.: RJ6AC1-MC08C1LSXSB26RLBxx

Cable Length: Customized lengthes

Connector Gender: Male to male double ended

Wire Gauge (size): 26AWG/ 0.14mm<sup>2</sup>

Keyway Coding: X-Coding

EMC Shielding: 360° fully shielded Straight/ 90° Angled: 180° Straight

## Product data

Contacts Poles:08 PinCable Length:Customized lengthesConnector Gender:Male to male double endedCable Jacket:PVCCurrent Rating:1 AWire Gauge (size):26AWG/ 0.14mm²Voltage Rating:48VWire Insulation:Foamed PEKeyway Coding:X-CodingEMC Shielding:360° fully shieldedStraight/ 90° Angled:180° StraightCable Color:GreenContacts Termination:Crimping, IDC piercingTemperature Rating:40°C ~ + 80°CContacts Material:Brass, machined solid pinCable Flamability:VW-1Contacts Plating:3μ" Gold plating thicknessCable Features:Anti-Vibration, Hydrolysis resistant, Oil resistantInserts:TPU + GFSealing:O-RingOvermolding:TPULocking Screws:Brass with nickel platedContact Resistance:5mΩInsulation Resistance:≥ 100 MΩProtection Degree:IP 67Insulation Resistance:≥ 100 MΩProtection Telamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)Charateristic Impedance:1000 4/-12Ethernet Catagory:Cat 6A (10Gbps/ 500Mhz)				
Current Rating:       1 A       Wire Gauge (size):       26AWG/ 0.14mm²         Voltage Rating:       48V       Wire Insulation:       Foamed PE         Keyway Coding:       X-Coding       EMC Shielding:       360° fully shielded         Straight/ 90° Angled:       180° Straight       Cable Color:       Green         Contacts Termination:       Crimping, IDC piercing       Temperature Rating:       -40°C ~ +80°C         Contacts Material:       Brass, machined solid pin       Cable Flamability:       VV-1         Contacts Plating:       3μ" Gold plating thickness       Cable Features:       Anti-Vibration, Hydrolysis resistant, Oil resistant         Inserts:       TPU + GF       Sealing:       O-Ring         Overmolding:       TPU + GF       Locking Screws:       Brass with nickel plated         Contact Resistance:       ≤5mΩ       Insulation Resistance:       ≥ 100 MΩ         Protection Degree:       IP 67       Pollution Degree:       III         Connector Flamability:       UL94 HB       Waterproof Depth:       IP67 1m depth 30 minutes         Plug Mating Life:       500 times       Warranty:       2-years quality guarantee period         Compliance:       RoHS compliant       Reference Standard:       IEC 61076-2-101, Profinet, EtherCAT         Co	Contacts Poles:	08 Pin	Cable Length:	Customized lengthes
Voltage Rating:       48V       Wire Insulation:       Foamed PE         Keyway Coding:       X-Coding       EMC Shielding:       360° fully shielded         Straight/ 90° Angled:       180° Straight       Cable Color:       Green         Contacts Termination:       Crimping, IDC piercing       Temperature Rating:       -40°C ~ + 80°C         Contacts Material:       Brass, machined solid pin       Cable Flamability:       VW-1         Contacts Plating:       3μ" Gold plating thickness       Cable Features:       Anti-Vibration, Hydrolysis resistant, Oil resistant         Inserts:       TPU + GF       Sealing:       O-Ring         Overmolding:       TPU       Locking Screws:       Brass with nickel plated         Contact Resistance:       ≤5mΩ       Insulation Resistance:       ≥ 100 MΩ         Protection Degree:       IP 67       Pollution Degree:       III         Connector Flamability:       UL94 HB       Waterproof Depth:       IP67 1m depth 30 minutes         Plug Mating Life:       500 times       Warranty:       2-years quality guarantee period         Compliance:       RoHS compliant       Reference Standard:       IEC 61076-2-101, Profinet, EtherCAT         Products Certification:       CE/ EMC, IP67       Connector Type:       Cable molding type (extension cable) <td>Connector Gender:</td> <td>Male to male double ended</td> <td>Cable Jacket:</td> <td>PVC</td>	Connector Gender:	Male to male double ended	Cable Jacket:	PVC
Keyway Coding:X-CodingEMC Shielding:360° fully shieldedStraight/ 90° Angled:180° StraightCable Color:GreenContacts Termination:Crimping, IDC piercingTemperature Rating:-40°C ~ +80°CContacts Material:Brass, machined solid pinCable Flamability:VW-1Contacts Plating:3μ" Gold plating thicknessCable Features:Anti-Vibration, Hydrolysis resistant, Oil resistantInserts:TPU + GFSealing:O-RingOvermolding:TPULocking Screws:Brass with nickel platedContact Resistance:≤5mΩInsulation Resistance:≥ 100 MΩProtection Degree:IP 67Pollution Degree:IIIConnector Flamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)	Current Rating:	1 A	Wire Gauge (size):	26AWG/ 0.14mm <sup>2</sup>
Straight/ 90° Angled:       180° Straight       Cable Color:       Green         Contacts Termination:       Crimping, IDC piercing       Temperature Rating:       -40°C ~ + 80°C         Contacts Material:       Brass, machined solid pin       Cable Flamability:       VW-1         Contacts Plating:       3μ" Gold plating thickness       Cable Features:       Anti-Vibration, Hydrolysis resistant, Oil resistant         Inserts:       TPU + GF       Sealing:       O-Ring         Overmolding:       TPU       Locking Screws:       Brass with nickel plated         Contact Resistance:       ≤5mΩ       Insulation Resistance:       ≥ 100 MΩ         Protection Degree:       IP 67       Pollution Degree:       III         Connector Flamability:       UL94 HB       Waterproof Depth:       IP67 1m depth 30 minutes         Plug Mating Life:       500 times       Warranty:       2-years quality guarantee period         Compliance:       RoHS compliant       Reference Standard:       IEC 61076-2-101, Profinet, EtherCAT         Products Certification:       CE/ EMC, IP67       Connector Type:       Cable molding type (extension cable)	Voltage Rating:	48V	Wire Insulation:	Foamed PE
Contacts Termination:Crimping, IDC piercingTemperature Rating:-40°C ~ + 80°CContacts Material:Brass, machined solid pinCable Flamability:VW-1Contacts Plating:3μ" Gold plating thicknessCable Features:Anti-Vibration, Hydrolysis resistant, Oil resistantInserts:TPU + GFSealing:O-RingOvermolding:TPULocking Screws:Brass with nickel platedContact Resistance:≤5mΩInsulation Resistance:≥ 100 MΩProtection Degree:IP 67Pollution Degree:IIIConnector Flamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)	Keyway Coding:	X-Coding	EMC Shielding:	360° fully shielded
Contacts Material:Brass, machined solid pinCable Flamability:VW-1Contacts Plating:3μ" Gold plating thicknessCable Features:Anti-Vibration, Hydrolysis resistant, Oil resistantInserts:TPU + GFSealing:O-RingOvermolding:TPULocking Screws:Brass with nickel platedContact Resistance:≤5mΩInsulation Resistance:≥ 100 MΩProtection Degree:IP 67Pollution Degree:IIIConnector Flamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)	Straight/ 90° Angled:	180° Straight	Cable Color:	Green
Contacts Plating:3μ" Gold plating thicknessCable Features:Anti-Vibration, Hydrolysis resistant, Oil resistantInserts:TPU + GFSealing:O-RingOvermolding:TPULocking Screws:Brass with nickel platedContact Resistance:≤5mΩInsulation Resistance:≥ 100 MΩProtection Degree:IP 67Pollution Degree:IIIConnector Flamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)	Contacts Termination:	Crimping, IDC piercing	Temperature Rating:	-40°C ~ + 80°C
Contacts Plating.Sp Gold plating thicknessCable Peatures.resistantInserts:TPU + GFSealing:O-RingOvermolding:TPULocking Screws:Brass with nickel platedContact Resistance:≤5mΩInsulation Resistance:≥ 100 MΩProtection Degree:IP 67Pollution Degree:IIIConnector Flamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)	Contacts Material:	Brass, machined solid pin	Cable Flamability:	VW-1
Overmolding:       TPU       Locking Screws:       Brass with nickel plated         Contact Resistance:       ≤5mΩ       Insulation Resistance:       ≥ 100 MΩ         Protection Degree:       IP 67       Pollution Degree:       III         Connector Flamability:       UL94 HB       Waterproof Depth:       IP67 1m depth 30 minutes         Plug Mating Life:       500 times       Warranty:       2-years quality guarantee period         Compliance:       RoHS compliant       Reference Standard:       IEC 61076-2-101, Profinet, EtherCAT         Products Certification:       CE/ EMC, IP67       Connector Type:       Cable molding type (extension cable)	Contacts Plating:	3μ" Gold plating thickness	Cable Features:	
Contact Resistance: $\leq 5m\Omega$ Insulation Resistance: $\geq 100 \ M\Omega$ Protection Degree: IP 67 Pollution Degree: III  Connector Flamability: UL94 HB Waterproof Depth: IP67 1m depth 30 minutes  Plug Mating Life: 500 times Warranty: 2-years quality guarantee period  Compliance: RoHS compliant Reference Standard: IEC 61076-2-101, Profinet, EtherCAT  Products Certification: CE/ EMC, IP67 Connector Type: Cable molding type (extension cable)	Inserts:	TPU + GF	Sealing:	O-Ring
Protection Degree:IP 67Pollution Degree:IIIConnector Flamability:UL94 HBWaterproof Depth:IP67 1m depth 30 minutesPlug Mating Life:500 timesWarranty:2-years quality guarantee periodCompliance:RoHS compliantReference Standard:IEC 61076-2-101, Profinet, EtherCATProducts Certification:CE/ EMC, IP67Connector Type:Cable molding type (extension cable)	Overmolding:	TPU	Locking Screws:	Brass with nickel plated
Connector Flamability: UL94 HB Waterproof Depth: IP67 1m depth 30 minutes  Plug Mating Life: 500 times Warranty: 2-years quality guarantee period  Compliance: RoHS compliant Reference Standard: IEC 61076-2-101, Profinet, EtherCAT  Products Certification: CE/ EMC, IP67 Connector Type: Cable molding type (extension cable)	Contact Resistance:	≤5mΩ	Insulation Resistance:	≥ 100 MΩ
Plug Mating Life: 500 times Warranty: 2-years quality guarantee period  Compliance: RoHS compliant Reference Standard: IEC 61076-2-101, Profinet, EtherCAT  Products Certification: CE/ EMC, IP67 Connector Type: Cable molding type (extension cable)	Protection Degree:	IP 67	Pollution Degree:	III
Compliance: RoHS compliant Reference Standard: IEC 61076-2-101, Profinet, EtherCAT  Products Certification: CE/ EMC, IP67 Connector Type: Cable molding type (extension cable)	Connector Flamability:	UL94 HB	Waterproof Depth:	IP67 1m depth 30 minutes
Products Certification: CE/ EMC, IP67 Connector Type: Cable molding type (extension cable)	Plug Mating Life:	500 times	Warranty:	2-years quality guarantee period
	Compliance:	RoHS compliant	Reference Standard:	IEC 61076-2-101, Profinet, EtherCAT
Charateristic Impedance: 100Ω +/-12 Ethernet Catagory: Cat 6A (10Gbps/ 500Mhz)	Products Certification:	CE/ EMC, IP67	Connector Type:	Cable molding type (extension cable)
	Charateristic Impedance:	100Ω +/-12	Ethernet Catagory:	Cat 6A (10Gbps/ 500Mhz)

## Description

CABLEFORCE offers tailor-made industrial PROFINET connecting cable cordsets. We are also supplying of other fieldbus cables compatible with most major fieldbus protocols, including CANopen, PROFIBUS, DeviceNet™, CAN Bus, CC-Link and ASI Bus and industrial EtherCAT, EtherNet/IP™ and other industrial Ethernet protocols with bandwidth from Cat 5e, Cat 6A to Cat7.

## We provide customers with the following cable custom services:

- Custom cable color and length, custom print and labeling as well as packaging
- Custom Material: Extreme Temperature Resistant, High Flexible, UV Resistance, Oil Resistance, LSZH, Hydrolysis Resistance, Anti-Corrosion;
- Connector Configuration: Single Ended, Double Ended, multi-Ended, multi-core wire, mixed joint and other configurations;
- Mechanical Reliable: Mating Life, EMI/EMC Shielding, Waterproof, Dustproof, Anti Vibration, Abrasion

Resistant, Bending Endurance, Drag Chain, Welding resistant, etc.;
• Transmission Performance: Bandwidth, Voltage and Current rating, Impedance and Measurement Accuracy, etc.

Cableforce Electronics | Tel:+ 86 769 8963 3851 | 2025-05-01