


M12 to DB9 RS232 Adapter Cable, M12 12Pin male, D-Sub 9Pin female, 26AWG shielded cable

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MC12C1LSASB24CKxx-DB09C2

Contacts Poles: 09 Pin, 12 Pin

Cable Length: Customized lengths

Connector Gender: Male to female connector, c

Cable Jacket: PVC

Voltage Rating: 30V

EMC Shielding: 360° fully shielded

Product data

| | | | |
|------------------------|--|---------------------|----------------------------|
| Contacts Poles: | 09 Pin, 12 Pin | Cable Length: | Customized lengths |
| Connector Gender: | Male to female connector, double ended | Cable Jacket: | PVC |
| Current Rating: | 1 A | Wire Gauge (size): | 26AWG/ 0.14mm ² |
| Voltage Rating: | 30V | Wire Insulation: | PVC |
| Keyway Coding: | A-Coding | EMC Shielding: | 360° fully shielded |
| Straight/ 90° Angled: | 180° Straight | Cable Color: | Black |
| Contacts Termination: | Soldering | Temperature Rating: | -25°C ~ + 80°C |
| Contacts Material: | Brass, machined solid pin | Cable Flamability: | VW-1 |
| Contacts Plating: | 3μ" Gold plating thickness | Cable Features: | UV-Resistant |
| Inserts: | TPU + GF | Overmolding: | TPU, PVC |
| Locking Screws: | Brass with nickel plated | Contact Resistance: | ≤10mΩ |
| Insulation Resistance: | ≥ 100 MΩ | Protection Degree: | IP 65 |
| Pollution Degree: | III | Plug Mating Life: | 100 times |
| Warranty: | 2-years quality guarantee period | Compliance: | RoHS compliant |
| Connector Type: | Cable molding type (extension cable) | | |

Description

Since the RS-232 is used beyond the original purpose of interconnecting the signals between a DTE and DCE, such as computer terminal and modem, Cableforce offers custom RS232 adapter cable solution for industrial application with M12 connector to D-Sub 9pin connector, enables the transfer the industrial data and signals to computers.

- M12 A-Coded male shielded connector, overmolded
- D-Sub 9Pin female connector, overmolded
- Cable specification and wiring can be customized