


M12 to DB9 RS232 Adapter Cable, M12 8Pin male, D-Sub 9Pin female, 8x24AWG shielded cable

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MC08C1LSASB24CK10-DB09C2
Contacts Poles: 08 Pin, 09 Pin
Cable Length: 1 m
Connector Gender: Male to female connector, double ended
Cable Jacket: PVC
Voltage Rating: 30V
EMC Shielding: 360° fully shielded
Products Certification: UL Certified

Product data

Contacts Poles:	08 Pin, 09 Pin	Cable Length:	1 m
Connector Gender:	Male to female connector, double ended	Cable Jacket:	PVC
Current Rating:	2 A	Wire Gauge (size):	24AWG/ 0.25mm ²
Voltage Rating:	30V	Wire Insulation:	PVC
Keyway Coding:	A-Coding	EMC Shielding:	360° fully shielded
Straight/ 90° Angled:	180° Straight	Cable Color:	Black
Contacts Termination:	Soldering	Temperature Rating:	-25°C ~ + 80°C
Contacts Material:	Brass, machined solid pin	Cable Flamability:	VW-1
Contacts Plating:	3μ" Gold plating thickness	Cable Features:	UV-Resistant
Inserts:	TPU + GF	Overmolding:	TPU, PVC
Locking Screws:	Brass with nickel plated	Contact Resistance:	≤10mΩ
Insulation Resistance:	≥ 100 MΩ	Protection Degree:	IP 65
Pollution Degree:	III	Plug Mating Life:	100 times
Warranty:	2-years quality guarantee period	Compliance:	RoHS compliant
Products Certification:	UL Certified	Connector Type:	Cable molding type (extension cable)

Description

Since the RS-232 is used beyond the original purpose of interconnecting the signals between a DTE and DCE, such as computer terminal and modem, Cableforce offers custom RS232 adapter cable solution for industrial application with M12 connector to D-Sub 9pin connector, enables the transfer the industrial data and signals to computers.

- M12 A-Coded male shielded connector, overmolded
- D-Sub 9Pin female connector, overmolded
- Cable specification and wiring can be customized