


M12 A-Code 8Pin male angled field wireable assembly type connector, screw connection, 4.0-7.0 mm, IP67

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MC08A1RWAB

Contacts Poles: 08 Pin

Connector Gender: Male connector

Current Rating: 1.5 A

Wire Gauge (size): 26AWG/ 0.14mm², 24AWG/

Keyway Coding: A-Coding

EMC Shielding: Un-shielded

Product data

Contacts Poles:	08 Pin	Connector Gender:	Male connector
Current Rating:	1.5 A	Wire Gauge (size):	26AWG/ 0.14mm ² , 24AWG/ 0.25mm ² , 22AWG/ 0.34mm ²
Voltage Rating:	30V	Keyway Coding:	A-Coding
EMC Shielding:	Un-shielded	Straight/ 90° Angled:	90° right angled
Contacts Termination:	Screwing	Temperature Rating:	-40°C ~ + 105°C
Contacts Material:	Brass, machined solid pin	Contacts Plating:	3μ" Gold plating thickness
Inserts:	PA66 + GF	Sealing:	O-Ring
Housing/ Outer Shell:	PA66 + GF	Locking Screws:	Brass with nickel plated
Contact Resistance:	≤5mΩ	Insulation Resistance:	≥ 100 MΩ
Protection Degree:	IP 67	Pollution Degree:	III
Connector Flamability:	UL94 V0	Waterproof Depth:	IP67 1m depth 30 minutes
Plug Mating Life:	500 times	Suitable Cable Diameter:	PG7 (4 ~ 6mm), PG9 (4.5 ~ 7mm)
Warranty:	2-years quality guarantee period	Compliance:	RoHS compliant, REACH compliant
Reference Standard:	IEC 61076-2-101	Connector Type:	Field assembly type

Description

The M12 metric size A-Coding connectors, based on IEC 61076-2-101 standard, it is the most commonly used connector in the factory automation. M12 A-Coding connectors mainly designed for sensor and actuator devices. CABLEFORCE M12 A-Coding connectors are developed and designed for harsh industrial and climatic environments, e.g. High temperature range endurance, Hydrolysis resistant, Oil resistant, Corrosion resistant, UV-Resistant, Abrasion resistant, Bending and Drag Chain applicable. M12 A-Coding is a specified single keyway design; differentiate itself from B, C, D, X, S, T, K, L, M, Y-Coding.

- Cableforce field wireable connector is available with contacts: 3pin, 4pin, 5pin, 8pin, 12pin
- We also sell the related bulk cables with unshielded, shielded, oil resistant, hydrolysis resistant, UV-resistant options
- The receptacle counter part with PCB contacts or Solder type panel mount connectors with wires
- Operating voltage 250V/ 60V/ 30V;
- Current range: 4A, 2A, 1.5A
- Degree of protection IP67