


7/8" Mini Change 5pin male to female double ended, with 5m 1Px18AWG+1Px15AWG5 DeviceNet Thick PVC violet cable

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MF05C3LCAB16CV50-DVN

Contacts Poles: 05 Pin

Cable Length: 5 m

Connector Gender: Male to female connector, c

Cable Jacket: PVC

Voltage Rating: 300V

EMC Shielding: Un-shielded

Products Certification: CE/ EMC

Product data

| | | | |
|------------------------|--|--------------------------|--|
| Contacts Poles: | 05 Pin | Cable Length: | 5 m |
| Connector Gender: | Male to female connector, double ended | Cable Jacket: | PVC |
| Current Rating: | 8 A | Wire Gauge (size): | 18AWG/ 0.75mm ² , 15AWG/ 1.5mm ² |
| Voltage Rating: | 300V | Wire Insulation: | PVC |
| Keyway Coding: | A-Coding | EMC Shielding: | Un-shielded |
| Straight/ 90° Angled: | 180° Straight | Cable Color: | Violet |
| Contacts Termination: | Crimping | Temperature Rating: | -40°C ~ + 80°C |
| Contacts Material: | Phosphor bronze, machined solid pin, Brass, machined solid pin | Cable Flamability: | VW-1 |
| Contacts Plating: | 3µ" Gold plating thickness | Cable Features: | UV-Resistant |
| Inserts: | TPU + GF | Sealing: | O-Ring |
| Overmolding: | TPU | Locking Screws: | Brass with nickel plated |
| Contact Resistance: | ≤5mΩ | Insulation Resistance: | ≥ 100 MΩ |
| Protection Degree: | IP 67 | Pollution Degree: | III |
| Connector Flamability: | UL94 V2 | Waterproof Depth: | IP67 1m depth 30 minutes |
| Plug Mating Life: | 500 times | Warranty: | 2-years quality guarantee period |
| Compliance: | RoHS compliant, REACH compliant | Products Certification: | CE/ EMC |
| Connector Type: | Cable molding type (extension cable) | Charateristic Impedance: | 120Ω +/-12 |

Description