


M8 4Pin female, right angled, molded 4x24AWG PUR cable, 1m, with pigtail

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MB04C2RSAB24RK10

Contacts Poles: 04 Pin

Cable Length: 1 m

Connector Gender: Female connector

Cable Jacket: PUR, halogen-free

Voltage Rating: 60V

EMC Shielding: Un-shielded

Products Certification: UL Certified, CUL Certi

Product data

Contacts Poles:	04 Pin	Cable Length:	1 m
Connector Gender:	Female connector	Cable Jacket:	PUR, halogen-free
Current Rating:	3 A	Wire Gauge (size):	24AWG/ 0.25mm ²
Voltage Rating:	60V	Wire Insulation:	PVC
EMC Shielding:	Un-shielded	Straight/ 90° Angled:	180° Straight
Cable Color:	Black	Contacts Termination:	Soldering
Temperature Rating:	-40°C ~ + 80°C	Contacts Material:	Phosphor bronze, machined solid pin
Cable Flammability:	VW-1	Contacts Plating:	3μ" Gold plating thickness
Cable Features:	UV-Resistant, Hydrolysis resistant, Oil resistant, Suitable for movable or drag chain cabling	Inserts:	TPU + GF
Overmolding:	TPU	Locking Screws:	Brass with nickel plated
Contact Resistance:	≤5mΩ	Insulation Resistance:	≥ 100 MΩ
Protection Degree:	IP 67	Pollution Degree:	III
Connector Flammability:	UL94 V2	Waterproof Depth:	IP67 1m depth 30 minutes
Plug Mating Life:	500 times	Warranty:	2-years quality guarantee period
Compliance:	RoHS compliant	Reference Standard:	IEC 61076-2-104
Products Certification:	UL Certified, CUL Certified, CE/ EMC, IP67, IP69K	Connector Type:	Cable molding type (extension cable)
Drag chain bending life:	2 million cycles		

Description

Cableforce M8 sensor cables are designed for industrial harsh and critical applications, CABLEFORCE provide with almost unlimited high-reliability circular sensor connectors and cables which are suited for various industrial applications of signals, data and power. The cable main features as following:

- Tailor made material to meet various application conditions
- Gold-plated solid brass or phosphor bronze contacts ≥ 500 times mating life
- Durable cable material suitable for Drag Chain moving and bending demands
- Good stripping and terminating properties
- Sturdy metal coupling screws with anti-vibration design, 48 hours Salt Spray Test
- UV Resistant, Hydrolysis Resistant□Oil resistant
- Temperature Range: Dynamic -25 ~ 80□, Static: -40 ~ 80□.
- Protection degree: IP67 in locked status, IP68 base on customer specific requirements.
- RoHS, REACH compliant.