


M12 A-Code 5Pin male to female, double ended, molded 1Px22AWG+ 1Px24AWG PVC CANBUS cable, 5m length

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MC05C3LSAB22CV50-CAN

Contacts Poles: 05 Pin

Cable Length: 5 m

Connector Gender: Male to female connector, c

Cable Jacket: PVC

Voltage Rating: 60V

EMC Shielding: Half or partial shielded

Products Certification: UL Certified, CUL Certi

Product data

Contacts Poles:	05 Pin	Cable Length:	5 m
Connector Gender:	Male to female connector, double ended	Cable Jacket:	PVC
Current Rating:	4 A	Wire Gauge (size):	22AWG/ 0.34mm ²
Voltage Rating:	60V	Wire Insulation:	PVC
Keyway Coding:	A-Coding	EMC Shielding:	Half or partial shielded
Straight/ 90° Angled:	180° Straight	Cable Color:	Violet
Contacts Termination:	Soldering	Temperature Rating:	-40°C ~ + 80°C
Contacts Material:	Phosphor bronze, machined solid pin, Brass, machined solid pin	Cable Flamability:	VW-1
Contacts Plating:	3µ" Gold plating thickness	Cable Features:	UV-Resistant, Suitable for movable or drag chain cabling
Inserts:	TPU + GF, PA66 + GF	Sealing:	O-Ring
Overmolding:	TPU	Locking Screws:	Brass with nickel plated
Contact Resistance:	≤5mΩ	Insulation Resistance:	≥ 100 MΩ
Protection Degree:	IP 67, IP 69K	Pollution Degree:	III
Connector Flamability:	UL94 HB	Waterproof Depth:	IP67 1m depth 30 minutes
Plug Mating Life:	500 times	Warranty:	2-years quality guarantee period
Compliance:	RoHS compliant	Reference Standard:	IEC 61076-2-101
Products Certification:	UL Certified, CUL Certified, CE/ EMC, IP67, IP69K	Connector Type:	Cable molding type (extension cable)
Charateristic Impedance:	120Ω +/-12		

Description

Cableforce M12 sensor cables are designed for industrial harsh and critical applications, CABLEFORCE provide with almost unlimited high-reliability circular sensor connectors and cables which are suited for various industrial applications of signals, data and power transmission. Cableforce's cable main features are:

- Tailor made material to meet various application conditions
- Gold-plated solid brass or phosphor bronze contacts ≥ 500 times mating life
- Durable cable material suitable for Drag Chain moving and bending demands
- Good stripping and terminating properties
- Sturdy metal coupling screws with anti-vibration design, 48 hours Salt Spray Test
- UV Resistant, Hydrolysis Resistant □ Oil resistant
- Temperature Range: Dynamic -25 ~ 80 □, Static: -40 ~ 80 □.

- Protection degree: IP67 in locked status, IP68 base on customer specific requirements.
- RoHS, REACH compliant.

Cableforce Electronics | Tel:+ 86 769 8963 3851 | 2024-05-15