


M8 6Pin female right angled connector molded with 6x26AWG cable, plastic screw

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MB06C2RSAP-26xx xx

Contacts Poles: 06 Pin

Connector Gender: Female connector

Cable Jacket: PVC, PUR, halogen-free, Custom

Current Rating: 1.5 A

Wire Gauge (size): 26AWG/ 0.14mm²

Keyway Coding: A-Coding

EMC Shielding: Un-shielded

Product data

| | | | |
|------------------------|--------------------------------------|-------------------------|---|
| Contacts Poles: | 06 Pin | Cable Length: | Customized lengths |
| Connector Gender: | Female connector | Cable Jacket: | PVC, PUR, halogen-free, Custom cable material |
| Current Rating: | 1.5 A | Wire Gauge (size): | 26AWG/ 0.14mm ² |
| Voltage Rating: | 30V | Wire Insulation: | PVC |
| Keyway Coding: | A-Coding | EMC Shielding: | Un-shielded |
| Straight/ 90° Angled: | 90° right angled | Cable Color: | Black |
| Contacts Termination: | Soldering | Temperature Rating: | -40°C ~ + 80°C |
| Contacts Material: | Phosphor bronze, machined solid pin | Cable Flamability: | VW-1 |
| Contacts Plating: | 3μ" Gold plating thickness | Cable Features: | UV-Resistant |
| Inserts: | TPU | Sealing: | O-Ring |
| Overmolding: | TPU | Locking Screws: | Nylon plastic |
| Contact Resistance: | ≤5mΩ | Panel Cut Size: | M8x1.0 |
| Insulation Resistance: | ≥ 100 MΩ | Protection Degree: | IP 67 |
| Pollution Degree: | III | Connector Flamability: | UL94 HB |
| Waterproof Depth: | IP67 1m depth 30 minutes | Plug Mating Life: | 500 times |
| Warranty: | 2-years quality guarantee period | Compliance: | RoHS compliant, REACH compliant |
| Reference Standard: | IEC 61076-2-104 | Products Certification: | UL Certified, CUL Certified, IP67, IP69K |
| Connector Type: | Cable molding type (extension cable) | | |

Description

M8 connector is a connector of 8mm metric size with thread locking mechanism, is one of the most commonly used connectors in factory automation, generally connecting with automation sensors in factory packaging and delivery system, outdoor LED module, security grating screen, and new energy signal control applications.

- 3 pin, 4 pin, 2P+2P, 5 pin, 6 pin, 8 pins available
- Custom cable specification and lengths, molded with PVC or PUR cable
- The receptacle counter part with PCB contacts or Solder type panel mount connectors
- Shielded, Oil-Resistant, Hydrolysis Resistant, UV-Resistant cable available
- Voltage rating: 60V, 30V
- Current rating: 4A, 3A, 1.5A
- IP67 protection degree
- Anti-vibration

