


M12 B-Code 5Pin male panel mount connector with PCB contacts, front side fastening, PG9/M16

Please be informed that the data shown in this PDF document is generated from our Online Catalog for reference only, for detailed technical information please contact our sales!



Part No.: MC05P1LPBBxx

Contacts Poles: 05 Pin

Connector Gender: Male connector

Current Rating: 4 A

Keyway Coding: B-Coding

Product data

Contacts Poles:	05 Pin	Connector Gender:	Male connector
Current Rating:	4 A	Voltage Rating:	60V
Keyway Coding:	B-Coding	Straight/ 90° Angled:	180° Straight
Contacts Termination:	PCB dip soldering	Temperature Rating:	-40°C ~ + 105°C
Contacts Material:	Brass, machined solid pin	Cable Flamability:	VW-1
Contacts Plating:	3μ" Gold plating thickness	Inserts:	PA66 + GF
Sealing:	Epoxy resin, O-Ring	Housing/ Outer Shell:	Brass with nickel plating
Locking Screws:	Brass with nickel plated	Contact Resistance:	≤5mΩ
Panel Cut Size:	PG9, M16x1.5	Insulation Resistance:	≥ 100 MΩ
Protection Degree:	IP 69K	Pollution Degree:	III
Connector Flamability:	UL94 V0	Waterproof Depth:	IP67 1m depth 30 minutes
Plug Mating Life:	500 times	Warranty:	2-years quality guarantee period
Compliance:	RoHS compliant, REACH compliant	Reference Standard:	IEC 61076-2-101
Products Certification:	UL Certified, CE/ EMC, IP67, IP69K	Connector Type:	Panel mount receptacle
Panel locking side:	Front side fastening the nut		

Description

The M12 metric size B-Coding connectors, it is commonly used connector in the Fieldbus cabling system, such as PROFIBUS cabling. M12 B-Coding connector designed with B specified single keyway coding structure which differentiates itself from A-, C-, D-, S-, T-, K-, L-Coding.

- Cable plugs, panel receptacles are available
- Cable specification base on customer requesting
- Degree of protection IP67
- 5 poles per connector
- Operating voltage 60V;
- Current range: 4A
- 360° EMI-Shielded
- Anti-vibration locking screw design