


## M8 Male, Field Wireable Connector, Right Angled

M8 公头 组装式 连接器 弯头

Male 公头



### Connector Technical data 技术参数

Contacts No. Pin位/芯数	3Pin	4Pin
Front View 正视图		
Reference Standard 参照标准	IEC 61076-2-104	
Rated current 额定电流	3A	
Rated voltage 额定电压	60V	
Impulse voltage 脉冲高压	1500V	
Locking system 锁紧方式	M8 x 1.0 screw / M8 螺丝锁紧	
Tightening Torque 螺丝扭矩	Recommend/ 建议: 0.2Nm, Max/ 最大: 0.4Nm, Wire screw/ 接线螺丝: 0.1Nm, Cable gland/ 尾卡螺母: 0.3-0.8Nm	
Termination 接线方式	Screw fixing / 锁螺钉	
Wire gauge 适配线规	0.25-0.34mm <sup>2</sup> (AWG 24~22)	
Cable outlet 适配线径	3.5-5mm	
Rated temperature 温度范围	-25 °C ... +80 °C	
Insulation resistance 绝缘电阻	≥ 100MΩ	
Contact resistance 接触电阻	≤ 5mΩ	
Connector body 外壳材料	PA66 + GF	
Contact carrier 胶芯材料	PA66 + GF	
Screw nut 螺丝材料	Brass, CNC, nickel-plated 黄铜 镀镍 机加工	
Contact Pin针端子	Brass/ 黄铜	
Contacts plating 端子镀层	Au (Gold) 镀金	
O-ring 密封圈	FKM/ NBR 氟橡胶/ 丁腈橡胶	
Protection degree 防护等级	IP67	
Pollution degree 污染等级	3	

### Ordering No. 订购料号

Poles 芯数	Male 公头	Female 母头
3 Pin	MB03A1RWAB	MB03A2RWAB
4 Pin	MB04A1RWAB	MB04A2RWAB

### Assembly Instruction 组装式安装说明

